

DHI-PHGIA2.61-SH

General Indoor Fixed LED



Features:

- 500x500mm, 500x750mm and 500x1000mm panel to match your design.
- Support hanging, stacked, wall-mounted, adapting to diverse environments
- Front and rear service, modules and PSU can be taken from the front totally..
- Dot by dot calibration ensures color richness and brightness uniformity, bringing excellent visual experience.



Technical Specification

Model

Model	DHI-PHGIA2.61-SH
-------	------------------

Parameters

Pixel Pitch	2.61mm	Ingress Protection	Front IP20/Rear IP20
Pixel Configuration	1R1G1B	Operating Temperature/ Humidity	-20 C~+40 C/10~90%RH
LED Type	SMD1515	Pixels per Cabinet	192x384 dots
Brightness	1000 cd/m ²	Contrast Ratio	5000:1
Viewing Angle	H160°/V140°	Frame Rate	50/60 Hz
Pixel Density	147,456 pixels/m ²	Refresh Rate	≥3840 Hz
Module Size	250x250 mm	Input Voltage	110~220V AC
Cabinet Size	500mmx1000mmx61.3 mm	Input Power (max)	450W/m ²
Cabinet Weight	9.0 kg	Input Power (typical)	160W/m ²
Area	0.5m ²	Installation	wall-mounted/hanging /stacking
Material	Aluminum	Maintenance Mode	Front/Rear Maintenance
Aspect Ratio	1:2	Lifespan	100,000h
Processing Depth	14 bits	Data Interconnection	Cat5 Cable (L≤100m),Single mode fiber (L≤10km)
Brightness Control	Manual/Automatic		